



THE DATASHEET OF BNCP-TRBJ3

PRODUCT SPECIFICATIONS

Part number: BNCP-TRBJ3

No. 0642688

Drawing number: K-1046480

Nominal 1 Standard MIL-C-39012(BNC)
MIL-PRF-49142(TRB)

2 Voltage rating AC 500V

3 Impedance Mismatch

4 Operating tempture range -40°C~+85°C

5 Operating humidity range 95%(Max.) ※No condensation



	Test Items	Test Method/Value	Remarks
1	E L E C T R I C A L	Insulation resistance	1000MΩ(Min.) at DC 250V
2		Withstanding voltage	1 minute at AC 500V
3		Contact resistance	Inner conductor : 3mΩ(Max.) Intermediate conductor : 0.5mΩ(Max.)(TRB) Outer conductor : 1mΩ(Max.)(TRB) Outer conductor : 3mΩ(Max.)(BNC)
4	M E C H A N I C A L	Compatibility	No defects or abnormalities
5		Tensile strength of coupling mechanism	250N(BNC) 444.82N(TRB)
6		Center contact retaining force	0.56N(Min.)(TRB)
	O T H E R S		

※The structural shape is shown in the attached drawing (Drawing number:K-1046480)

	REVISIONS	DATE
1		
2		
3		

Checked	Approved	Inspected	Prepared
三 24.07.17 村	檜 24.07.17 澤	石 24.07.17 川	井 24.07.17 出

GKQM-24

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View BNCP-TRBJ3](#) on WIN SOURCE

 [TYCLON](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management