



THE DATASHEET OF IDSD-06-S-12.00-ST3

-T PLATING	-G GRAY CABLE	-ST"X" STRIPPED & TINNED	-WXX WIRING REVERSED	-BXX BREAKOUT																
-T: TIN BOTH ENDS -USE C-10-T	SUBSTITUTE GRAY CABLE FOR STANDARD COLOR CODED CABLE. USE: IDSD: CB-XX-28-7/36-050-G IDSS: CB-XX-28-7/36-100-G (SEE FIG. 1) NOTE: USE GRAY CABLE FOR DOUBLE ROW -31 THRU -36 POSITION.	<table><tr><td></td><td>"L"</td><td></td></tr><tr><td>ST8</td><td>1/8</td><td>[3.18]</td></tr><tr><td>ST4</td><td>1/4</td><td>[6.35]</td></tr><tr><td>ST3</td><td>3/8</td><td>[9.53]</td></tr><tr><td>ST2</td><td>1/2</td><td>[12.70]</td></tr></table> NOTES: 1. CONDUCTORS SHALL BE CONSISTENT IN APPEARANCE. SOLDER MUST MAINTAIN CABLE STRAINS WITHIN THE MAX DIA. TOLERANCE. 2. USE 60/40 TIN/LEAD SOLDER ONLY. 3. NOT AVAILABLE IN 28 POSITION AND UP IN DOUBLE ROW ONLY. L ± 1/16 [1.59] .030 [.76] MAX. DIA. (AFTER STRIPPED & TINNED) 1/16 [1.59] MAX. FLAT WIRE ALLOWED SEE NOTE 1.		"L"		ST8	1/8	[3.18]	ST4	1/4	[6.35]	ST3	3/8	[9.53]	ST2	1/2	[12.70]	SAME AS -SXX EXCEPT OUTER STRIP CONNECTED TO CONDUCTOR #2 AND INSIDE STRIP CONNECTED TO CONDUCTOR #1	3" ± 2 1/16" [76 ± 51] BROWN WIRE IDSD-XX-D-XX-BXX XX INDICATES NO. OF CONDUCTORS IDSD-XX-S-XX-BXX XX INDICATES NO. OF CONDUCTORS IDSS-XX-D-XX-BXX: XX INDICATES NO. OF POSITIONS IDSS-XX-S-XX-BXX: XX INDICATES NO. OF POSITIONS	
	"L"																			
ST8	1/8	[3.18]																		
ST4	1/4	[6.35]																		
ST3	3/8	[9.53]																		
ST2	1/2	[12.70]																		
-DXX IDSS N/A DAISY CHAIN- DOUBLE	-PXX POLARIZED MATING	-R REVERSED CONNECTOR NOT AVAILABLE WITH -M & -O	-M MIDDLE REVERSED NOT AVAILABLE WITH -R & -O	-O OUTSIDE REVERSED NOT AVAILABLE WITH -R & -M																
XX ± 1/8 (MIN 2") [XX ± 3.18] (MIN 51mm) BROWN WIRE FIRST PRESS END NOTE: 2" MINIMUM LENGTH 1" INCREMENTS ONLY	XX=POSITION NO. INSERT POLARIZING KEY PART NO. PK-06 INTO SPECIFIED POSITION -XX 1 3 71 2 4 72 BROWN WIRE 1 36 BROWN WIRE NOTE POLARIZED POSITION WILL HAVE SAME ELECTRICAL POSITION FROM BROWN WIRE.	1 3 71 2 4 72 BROWN WIRE 1 36 BROWN WIRE BOTH SOCKETS REV. WHEN DAISY CHAINED	1 3 71 2 4 72 BROWN WIRE 1 36 BROWN WIRE STANDARD WIRING BROWN WIRE INDICATES PIN #1 FIRST POSITION BROWN WIRE BROWN WIRE TO OPPOSITE SIDE OF FIRST POSITION -RW REVERSED WIRING																	
		-SXX DAISY CHAIN- SINGLE																		
		XX ± 1/8 (MIN 2") [XX ± 3.18] (MIN 51mm) BROWN WIRE FIRST PRESS END NOTE OPTION -SXX WHEN MATING DOUBLE ROW CONNECTOR WITH 2 SINGLE ROW CONNECTORS, THE OUTER MOST SINGLE WILL BE CONNECTED TO CONNECTOR #1 AND THE INSIDE SINGLE TO CONNECTOR #2.																		
				520 PARK EAST BLVD. NEW ALBANY, INDIANA 47150 PHONE (812) 944-6733 P.O. BOX 1147 CODE 55322																
				IDSX-XX-X-XX-XXX-XXX SHEET 2 OF 2																

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF SAMTEC INC.

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF SAMTEC INC.

F:\EP\CABLE
IDSXASM2

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View IDSD-06-S-12.00-ST3](#) on WIN SOURCE

 [Samtec Inc.](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management